

# POWER TROWELS

## Applications:

- Electric trowel
- Concrete surfacing
- For all applications sizes
- Capacity machines
- Floors, slabs

## Features:

- Safety belt-clutch with Atlas Copco "Quick Stop"
- Variable speed on petrol models

- Adjustable handle
- Quick release blades available
- Easy to clean

## Accessories:

- Trowel blades
- Discs



CONCRETE EQUIPMENT



## Walk-behind trowels

Petrol versions

Power trowels	BG375	BG375	BG375	BG375	BG375	BG375	BG475	BG475	BG475	
Protection ring diameter	mm	950	84	80	950	950	1200	1200	1200	
Operating weight	kg	83	84	80	900	900	102	102	80	
Blade diameter	mm	900	900	900	945	945	1140	1140	1140	
D sc diameter	mm	945	945	945	945	945	-	-	-	
Floating blade diameter	mm	945	945	945	945	945	1160	1160	1160	
Blade speed	rpm	40-140	40-115	40-140	40-140	40-115	40-140	40-115	40-140	
Number of blades		4	4	4	4	4	4	4	4	
Type of handle		Foldable	Foldable	Rigid	Foldable	Long	Foldable	Long	Rigid	
Pitch control		Twist-Pitch	Twist-Pitch	Twist-Pitch	Twist-Pitch	Twist-Pitch	Twist-Pitch	Twist-Pitch	Twist-Pitch	
Clutch type		Centrifugal	Quickstop	Centrifugal	Centrifugal	Quickstop	Quickstop	Quickstop	Centrifugal	
Lifting hook		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Transport wheels		Accessory	Accessory	Accessory	Accessory	Accessory	Accessory	Accessory	Accessory	
Blade arm type		Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	Quick release / Bolt-on	
<b>Engine</b>										
Engine brand		Honda	Honda	Briggs&Stratton	Honda	Honda	Honda	Honda	Eriggs&Stratton	
Nodel		GX160	GX160	750 series	GX200	GX270	GX270	GX270	1450 series	
Power	hp	5	5	5	6	9	9	9	9	
Fuel		Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol	
Fuel tank capacity	l	3.1	3.1	5.3	3.1	5.3	5.3	5.3	5.3	
Vibrations	m/s2	3.5	3.5	4.8	3.5	3.2	3.2	3.2	4.8	
Sound power level, guaranteed	L <sub>wa</sub> dB(A)	106	106	106	106	106	106	106	106	
Sound pressure level at operator's position	L <sub>pA</sub> dB(A)	92	92	92	92	92	92	92	92	
Nodel code		H5 F CC TP	H5 F BC TP	V5 S CC TP	H6 F CC TP	H6 L BC TP	H9 F CC TP	H9 L BC TP	V9 S CC TP	
Part number		4812_0554_10	4812_0554_18	4812_0554_23	4812_0554_11	4812_0554_19	4812_0554_20	4812_0554_14	4812_0554_21	