

## PNEUMATIC BREAKERS TEX 32-TEX 40

34-42 kg

### Applications:

- Heavy-duty demolition breakers for use in medium and hard materials such as asphalt and reinforced concrete

### Features:

- Noise-reduction
- HAPS™ Hand and Arm Protection System (PE series)
- Rotating air inlet swivel
- Integrated lubricator
- Air cushioned piston



HANDHELD  
PNEUMATICS

Pneumatic breakers	TEX 32PS		TEX 33PE		TEX 39PS		TEX 40PE	
Weight	kg	34	37	37	39	39	42	42
Length	mm	745	745	745	750	750	750	750
Air consumption	l/s	34	34	34	40	40	40	40
Impact rate	blows/min	1200	1200	1200	1110	1110	1110	1110
Vibration level 3 axes (ISO 28927-10)	m/s <sup>2</sup>	13,7	5,7	5,7	14,3	14,3	4,2	4,2
Sound power level guaranteed (2000/14/EC)	L <sub>w</sub> dB(A)	111	111	111	111	111	111	111
Sound pressure level (ISO 11203)	L <sub>p</sub> , r=1m	99	99	99	99	99	99	99
Shank size	Hex mm	28x160	28x160	32x160	28x160	32x160	28x160	32x160
Part number		8461 0227 03	8461 0227 01	8461 0227 00	8461 0228 03	8461 0228 01	8461 0228 05	8461 0228 04

Data at 6 bar (90 psi) air pressure.  
Unsilenced models TEX 32P and TEX 39P available on request in some markets.

Claw couplings not included in delivery.

Suitable couplings:

Atlas Copco Standard 9000 0306 00  
Atlas Copco Standard with strainer 9000 0306 01  
US Standard 9001 0005 06