

DOUBLE DRUM ROLLER

Applications:

- Compacting thin layers of granular soils, wet sand and asphalt
- Jobs in confined areas, parking lots, repair works etc

Advantages:

- High efficiency
- Reliable
- Long life
- Easy to operate
- Hydraulic-oil cooler for increased lifetime of vital components
- Heavy-duty protection frame and single lifting point for easy transportation

Features:

- Fully hydraulic propulsion and vibration
- Large, removable water tank
- Minimum overhang on both sides and high curb clearance
- Powerful engine for reliable operations



COMPACTOR
EQUIPMENT

NEW Q2 2016

Duplex roller		LP6505		LP7505	
Filel		Diesel	Diesel	Diesel	Electric start
Starter type		Manual start	Electric start	Manual start	Electric start
Operating weight	kg	745	765	981	1001
Frequency	Hz	58	58	57	57
Amplitude	mm	0,52	0,52	0,54	0,54
Centrifugal force	kN	21,8	21,8	27,3	27,3
Speed, forward/reverse	km/h	0-3,6	0-3,6	0-3,6	0-3,6
H/A vibrations, standard handle	m/s ²	4,1	4,1	2,6	2,6
Sound power, guaranteed	dB(A)	107	107	107	107
Sound pressure at operators ear	dB(A)	88	88	88	88
Dimensions					
Drum diameter	mm	400	400	400	400
Drum width	mm	650	650	750	750
LxWxH	mm	1110/2500x720x1215	1110/2500x720x1215	1110/2500x820x1260	1110/2500x820x1260
Engine					
Model		Hatz 1D42S	Hatz 1D42S	Hatz 1D50S	Hatz 1D50S
Rated power	kW	7,2	7,2	7,9	7,9
Part number		3382 0002 22	3382 0002 20	3382 0002 44	3382 0002 45