

PNEUMATIC POKERS



Applications:

- Concrete vibration
- Low to high slump concrete
- Floors, slabs, pillars, columns, walls

Features:

- Low air consumption
- Diameter from 25 up to 155 mm
- Ball stop handle
- Air filter on ball stop
- Hose available in 2, 4 & 6 m up Ø77 mm

Advantages:

- Several pokers can be run by one air compressor
- Available in different lengths
- From Ø25mm up to 155 mm

Accessories:

- Atlas Copco hose
- Atlas Copco lubricator

CONCRETE
EQUIPMENT



AY Pokers	AY27	AY37	AY47	AY57	AY67	AY77	AY87	AY107	AY157
Tube diameter	26	36	47	56	67	77	87	108	155
Tube length	254	267	316	344	365	398	410	415	430
Tube weight	0,7	1,5	2,8	4,5	7,9	8,9	9,7	17,7	28
Frequency	12000	12000	12000	12000	12000	12000	12000	12000	12000
Hose length	-	-	-	-	-	-	1,5	1,5	0,8
Air consumption	0,36	0,46	0,7	1	1	1,3	1,6	1,9	2,7
Vibration value	0,5	1,0	2,4	2,1	2,1	2,4	1,9	2,9	12,3
Noise level	84,5	89,2	95,8	95,0	94,0	98,0	94,0	96,3	92,4
Part number									
Hose length	2 m	4812 0508 13	4812 0508 19	4812 0508 20	4812 0508 21	4812 0508 22	4812 0508 23	4812 0508 24	4812 0508 26
Hose length	4 m	4812 0508 81	4812 0508 83	4812 0508 85	4812 0508 87	4812 0508 89	4812 0508 91	-	-
Hose length	6 m	4812 0508 82	4812 0508 84	4812 0508 86	4812 0508 88	4812 0508 90	4812 0508 92	-	-